



HiMAX 6

390~405W

210mm Cells Mono
PERC with MBB & Half-cut
Technology

Quality Guarantee

12-year Warranty for Materials and Processing
25-year Warranty for Extra Linear Power Output



21.1%
Max Module Eff.

0~+5W
Positive Tolerance

Complete System and Product Certifications

IEC 61215, IEC 61730, UL 61730
ISO 9001:2008: ISO Quality Management System
ISO 14001: 2004: ISO Environment Management System
OHSAS 18001: 2007 Occupational Health and Safety



* Specifications subject to technical changes and tests. Sunpal Solar reserves the right of interpretation.

Positive power tolerance (0~+5W) guaranteed

High module conversion efficiency (up to 21.1%)

Slower power degradation enabled by Low LID Mono PERC technology: first year <2%, 0.55% year 2-25

Solid PID resistance ensured by solar cell process optimization and careful module BOM selection

Reduced resistive loss with lower operating current

Higher energy yield with lower operating temperature


Reduced hot spot risk with optimized electrical design and lower operating current



Add: West Changjiang Road, Shushan District, Hefei City, Anhui Province, China.
Email: info@sunpalsolar.com Tel: +86 551 6586 5992
WhatsApp: +86 180 5513 2023 Web: www.sunpalsolar.com



Design (mm)



Cell Orientation	120(5x24)
Junction Box	IP68, three diodes
Output Cable	4mm ² , 300mm in length, length can be customized
Glass	Single glass 3.2mm coated tempered glass
Frame	Anodized aluminum alloy frame
Weight:	21.3kg±3%
Dimension	1754x1096x30mm
Packaging	36pcs per pallet 930pcs per 40'ft Container

Operational Temperature	-40°C~+85°C
Power Output Tolerance	0~+4.99W
Voc & Isc Tolerance	±3%
Max. System Voltage	DC1500V(IEC/UL)
Max. Series Fuse Ratin	20A
NOCT	45±2°C
Safety Class	II
Fire Rating	UL type 1 or 2
Max. Static Load(Front)	5400Pa
Max. Static Load(Back)	2400Pa

Electrical Characteristics

Model Number	SP390M-60H		SP395M-60H		SP400M-60H		SP405M-60H	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	390	295	395	298	400	302	405	306
Open Circuit Voltage (Voc/V)	40.80	38.40	41.00	38.60	41.20	38.8	41.40	38.90
Short Circuit Current (Isc/A)	12.14	9.78	12.21	9.84	12.28	9.90	12.34	9.69
Voltage at Maximum Power (Vmp/V)	33.80	31.80	34.00	32.00	34.20	32.20	34.40	32.50
Current at Maximum Power (Imp/A)	11.54	9.26	11.62	9.32	11.70	9.38	11.77	9.41
Module Efficiency(%)	20.3		20.5		20.8		21.1	
Temperature Coefficient of Isc								
Temperature Coefficient of Voc	+0.05%/°C							
Temperature Coefficient of Pmax	-0.28%/°C							
	-0.36%/°C							

* STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25°C, Spectra at AM1.5

* NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20°C, Spectra at AM1.5, Wind at 1m/s

* Test uncertainty for Pmax: ±3%

I-V Curve

